



COLORado 2 Tour



Regular Price: \$1999.99

Sale Price: \$1399.99

Features

- 3, 4, 5, or 9-channel LED wash light (with ID addressing)
- Operating modes
 - 3-channel: RGB control
 - 3-channel: HSV control
 - 4-channel: RGBW control
 - 4-channel: RGB, dimmer
 - 5-channel: RGBW, dimmer
 - 9-channel: RGBW, ID, dimmer, strobe, macro, auto, custom
- RGBW color mixing with or without DMX controller
- Color temperature presets (3,200 K ~ 10,000 K)
- Built-in automated programs via DMX or COLOR-CON
- Recall custom programs via DMX
- High-power, 2 W ~ 3 W (750 mA ~ 1,000 mA) LEDs
- Ingress Protection: IP66
- Additional power output: max 7 units @ 120 V (see manual for details)
- Adjustable barn doors to direct output (includes gel frame)
- LED display with lock-out feature

OPTIONS

- COLORado™ Controller (COLOR-CON)
 - Optical systems: 15° (installed), 30° (CL20X30)
 - 16.4

Specifications

- Installed optics: 15° optics
 - Beam angle: 11°
 - Field angle: 23°
 - Lux: 15,060.91 @ 2 m
- Optional Optics: 30° optics
 - Beam angle: 28°
 - Field angle: 57°
 - Lux: 2,552.57 @ 2 m
- Light source: 48 (12 x 750 mA red, 12 x 1,000 mA green, 12 x 1,000 mA blue, 12 x 1,000 mA white) LEDs, 50,000hrs
- Power and current:
 - 120 V, 60 Hz; 179.4 W, 1.43 A (operating), 0.75 A (inrush)
 - 230 V, 50 Hz; 178.9 W, 0.78 A (operating), 0.81 A (inrush)
- AC power: Auto-ranging 100 V ~ 240 V 50/60 Hz
- Power cable with plug: 65 in (1,651 mm)
- IP66 power extension cable: 103 in (2,604 mm)
- IP66 signal extension cable: 103 in (2,604 mm)
- DMX input cable: 6.5 in (165 mm)
- DMX output cable: 6.5 in (165 mm)
- Weight: 20 lbs
 - 9.1 kg
- Size: 9 x 12 x 10.9 in
 - 230 x 305 x 276 mm