



COLORado 3p



Regular Price: \$1149.99

Sale Price: \$799.99

Features

- 3, 4, 9, or 12-channel LED bank system (with ID addressing)
- Operating modes:
 - 3-channel: RGB control
 - 4-channel: RGB, dimmer
 - 9-channel: RGB, ID, dim, macro, strobe, automatic, custom, DMX modes
 - 9-channel: RGB of 3 separate sections
 - 12-channel: RGB, CMY, ID, dim, macro, strobe, automatic, custom, DMX modes
- Individual pod control
- Pre-programmed color macros for each section
- RGB color mixing with or without DMX controller
- Built-in automated programs via DMX or COLOR-CON
- High-power, 1 W (350 mA) LEDs
- Ingress Protection: IP66
- Interlock multiple units to create blinder, wall, or strip light effects
- Additional power output: max 15 units @ 120 V (see manual for details)
- LCD display with password protection

OPTIONS

- COLORado Controller (COLOR-CON)
- Optical systems: 15° (installed), 30° (C-LENS3018)
- 16.4 ft (5 m) power extension cable (IP5POWER)
- 16.4 ft (5 m) signal extension cable (IP5SIG)

Specifications

- 15° optics
 - Beam angle: 14.4°
 - Field angle: 30.8°
 - Lux: 4,070.81 @ 2 m
- 30° optics
 - Beam angle: 33.6°
 - Field angle: 61.3°
 - Lux: 859.6 @ 2 m
- Light source: 54 (18 x 350 mA red, 18 x 350 mA green, 18 x 350 mA blue) LEDs, 50,000 hrs
- Power and current: 120 V, 60 Hz; 88 W, 0.6 A (operating), 1.2 A (inrush)
- Power and current: 230 V, 50 Hz; 87.9 W, 0.39 A (operating), 0.73 A (inrush)
- AC power: Auto-ranging 100 V ~ 240 V 50/60 Hz
- IP66 power extension cable: 103 in (2,604 mm)
- IP66 signal extension cable: 103 in (2,604 mm)
- DMX input cable: 6.5 in (165 mm)
- DMX output cable: 6.5 in (165 mm)
- Power in: 21.5 in (546 mm)
- Power out: 20 in (508 mm)
- Data in: 22 in (559 mm)
- Data out: 18 in (470 mm)
- Power cable with plug: 65 in (1,651 mm)
- Weight: 18 lbs / 8.2 kg
- Size: 22.5 x 7.5 x 8.3 in / 570 x 190 x 210 mm