



COLORado 6p



Regular Price: \$1999.99

Sale Price: \$1399.99

Features

- 3, 4, 9, or 12-channel indoor / outdoor RGB LED bank system
- Operating modes
 - 3-channel: RGB control
 - 4-channel: RGB, dimmer
 - 9-channel: RGB, ID addressing, dimmer, macro, strobe, auto / custom, DMX modes
 - 9-channel: RGB of 3 separate sections
 - 12-channel: RGB, CMY, ID addressing, dimmer, macro, strobe, auto / custom, DMX modes
- Individual pod control
- Pre-programmed color macros for each section
- RGB color mixing with or without DMX control
- Built-in automated programs via DMX or COLOR-CON
- Ingress Protection: IP66
- Interlock multiple units to create blinder, wall, or strip light effects
- Additional power output: max 8 units @ 120 V
- LCD display with password protection

Specifications

- Installed optics: 15°
 - Beam angle: 13°
 - Field angle: 26°
 - Lux: 10,661 @ 2 m
- Optional optics: 30°
 - Beam angle: 29.5°
 - Field angle: 55.4°
 - Lux: 2,394 @ 2 m
- Light source: 108 x 1 W LEDs 50,000 hrs (36 x 350 mA red, 36 x 350 mA green, 36 x 350 mA blue)
- Power and current:
 - 120 V, 60 Hz; 175.8 W, 1.2 A (operating), 2.6 A (inrush)
 - 230 V, 50 Hz; 177.3 W, 0.78 A (operating), 0.24 A (inrush)
- AC power: Auto-ranging 100 V ~ 240 V 50/60 Hz
- Power cable with plug: 65 in (1,651 mm)
- IP66 power extension cable: 103 in (2,604 mm)
- IP66 signal extension cable: 103 in (2,604 mm)
- DMX input cable: 6.5 in (165 mm)
- DMX output cable: 6.5 in (165 mm)
- Data in: 22 in (559 mm)
- Data out: 18 in (470 mm)
- Power in: 21.5 in (546 mm)
- Power out: 20 in (508 mm)
- Weight: 28.7 lbs / 13.3 kg
- Size: 7.5 x 22.4 x 8.7 in / 190 x 570 x 220 mm